

PMR Bluetooth Class 1 USB Adapter



Retail contents include:-

- Class 1 USB Adapter (100m range)
- Install CD
- Quick Start Guide

System Requirements:-

PC compatible computer with CPU speed 200Mhz or above. memory 64MB or above, 128MB recommended and Microsoft Windows 98SE/ME/2000/XP

The PMR, Class 1, USB adapter is fully compatible with Bluetooth 1.1,1.2 and 2.0. Software supplied supports Win98, ME, 2000,XP

| Model Name | | | | | | | PMR-0333R | | |
|------------|--|--|--|--|---|--|-----------|--|--|
| | | | | | - | | _ | | |

Product Name Bluetooth USB Adapter (or Dongle)

Chipset Broadcom BCM2045
Certification FCC, CE, ROHS
Standard Bluetooth V2.0

Frequency Band 2.4~2.4835GHz unlicensed ISM band

Modulation Method GFSK, 1Mbps, 0.5BT Gaussian

Spread Spectrum FHSS (Frequency Hopping Spread Spectrum)

Transfer rates (Max) Max UART baud rates of 3Mbps

RF Output Power Class 1

Working distance Greater than 100m in free space

Sensitivity <-82dBm at < 0.1% BER
Antenna Ceramic Antenna
Input power DC 5V (via USB Port)

I/O Interface USB

LED indicator Power / Active

Serial Port, Dial Up Networking, Fax, Headset,

Services supported PIM Item Transfer, PIM Synchronisation,

File Transfer, Network Access, Audio Gateway, HID

OS Support Windows Win 98SE / Me / 2000 / XP, Mac 10.3.5

Operation temperature: 0 oC ~ + 60 oC

Environment Storage temperature: -10 oC ~ +70 oC

Humidity: 5 ~ 90% non-condensing

Size 49.36 (L) x 17.99(W) x 7.55(H) mm

Weight 6.3 g



For further information contact

www.pmrtechnology.co.uk or

email

info@pmrtechnology.co.uk

Preliminary Specification revision B 1/6/2006 Specifications subject to change without notice and PMR accept no liability for any inaccuracy All trademarks recognised

