

PMR Bluetooth 2.0 EDR Class 2 USB Adapter



Retail contents include:-

- Class 2 USB Adapter (10m range)
- Install CD
- Quick Start Guide

System Requirements:-

PC compatible computer with CPU speed 200Mhz or above, memory 64MB or above, 128MB recommended and Microsoft Windows 98SE/ME/2000/XP

The PMR, Class 2, USB adapter is fully compatible with Bluetooth 1.1, 1.2 and 2.0. Software supplied supports Win98, ME, 2000, XP

Model Name	PMR-0333E
Product Name	Bluetooth USB Adapter (or Dongle)
Chipset	Broadcom BCM2045
Certification	FCC, CE
Standard	Bluetooth V2.0
Frequency Band	2.4~2.4835GHz unlicensed ISM band
Modulation Method	GFSK, 1Mbps, 0.5BT Gaussian
Spread Spectrum	FHSS (Frequency Hopping Spread Spectrum)
Transfer rates (Max)	Max UART baud rates of 3Mbps
RF Output Power	Class 2
Working distance	Greater than 10m in free space
Sensitivity	<-82dBm at < 0.1% BER
Antenna	Ceramic Antenna
Input power	DC 5V (via USB Port)
I/O Interface	USB
LED indicator	Power / Active
Services supported	Serial Port, Dial Up Networking, Fax, Headset, PIM Item Transfer, PIM Synchronisation, File Transfer, Network Access, Audio Gateway, HID
OS Support	Windows Win 98SE / Me / 2000 / XP, Mac 10.3.5
Environment	Operation temperature: 0 oC ~ + 60 oC Storage temperature: -10 oC ~ +70 oC Humidity: 5 ~ 90% non-condensing
Size	49.36 (L) x 17.99(W) x 7.55(H) mm
Weight	6.3 g



For further information
contact
www.pmrtechnology.co.uk or
email
info@pmrtechnology.co.uk

Preliminary Specification revision A 1/08/2005
Specifications subject to change without notice and PMR accept no liability for any inaccuracy
All trademarks recognised